



HS2100/HS3100 Series Wired/Bluetooth Rugged Headset Technical Accessory Guide







NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.




This document and the information contained therein (Information) are Zebra- confidential, and are provided under, and subject to, the confidentiality provision of your PartnerConnect agreement with Zebra. Any public disclosure (via posting on your website or otherwise) of the Information is strictly prohibited and will be considered a violation of your PartnerConnect agreement with Zebra.

* Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.


Headsets

Part Number	Picture	Description	Notes	Required Items
HS2100-OTH		HS2100 Rugged Wired Headset (Over the Head headband)	<ul style="list-style-type: none"> ► Includes HS2100 Boom Module (HS2100-BOOM-01) and HSx100 Over the Head (OTH) Headband Module (HSX100-OTH-HB-01) ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation for a superior voice experience in the noisiest environments ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene 	Audio Cable from list below. HS2100 does not include any cable to connect to the mobile device. The cable must be purchased separately.
HS2100-BTN-L		HS2100 Rugged Wired Headset (Behind the Neck headband)	<ul style="list-style-type: none"> ► Includes HS2100 Boom Module (HS2100-BOOM-01) and HSx100 Behind the Neck (BTN) Module (HSX100-BTN-L-HB-01) ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation for a superior voice experience in the noisiest environments ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene 	Audio Cable from list below. HS2100 does not include any cable to connect to the mobile device. The cable must be purchased separately.



HS2100-BOOM-01		HS2100 Rugged Wired Headset Boom Module	<ul style="list-style-type: none"> ► Includes HS2100 Boom Module with windscreen ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation for a superior voice experience in the noisiest environments ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing users to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene 	<ul style="list-style-type: none"> ► Headband Module (HSX100-OTH-HB-01 or HSX100-BTN-L-HB-01) ► Audio Cable from list below. HS2100 does not include any cable to connect to the mobile device. The cable must be purchased separately.
HS3100-OTH		HS3100 Rugged Bluetooth Headset (Over the Head headband)	<ul style="list-style-type: none"> ► Includes HS3100 Boom Module (HS3100-BOOM-01) and HSx100 Over the Head (OTH) Headband Module (HSX100-OTH-HB-01) ► HD Voice, also known as Wide Band Audio, brings incredible audio clarity ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation for a superior voice experience in the noisiest environments ► Swap batteries on the fly — without losing the Bluetooth connection ► Split-second tap-to-pair simplicity using NFC. ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing users to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene ► 15 hours of battery power 	

HS3100-BTN-L		HS3100 Rugged Bluetooth Headset (Behind the Neck Headband Left)	<ul style="list-style-type: none"> ► Includes HS3100 Boom Module (HS3100-BOOM-01) and HSx100 Behind the Neck (BTN) Module (HSX100-BTN-L-HB-01) ► HD Voice, also known as Wide Band Audio, brings incredible audio clarity ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation for a superior voice experience in the noisiest environments ► Swap batteries on the fly — without losing the Bluetooth connection ► Split-second tap-to-pair simplicity using NFC. ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene ► 15 hours of battery power 	
HS3100-BOOM-01		HS3100 Rugged Bluetooth Headset Boom Module	<ul style="list-style-type: none"> ► Includes HS3100 Boom Module with battery and windscreen ► HD Voice, also known as Wide Band Audio, brings incredible audio clarity ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation for a superior voice experience in the noisiest environments ► Swap batteries on the fly — without losing the Bluetooth connection ► Split-second tap-to-pair simplicity using NFC. ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene ► 15 hours of battery power 	Headband Module (HSX100-OTH-HB-01 or HSX100-BTN-L-HB-01)
Communication Cables (for HS3100)				
Part Number	Picture	Description	Notes	Required Items
CBL-HS3100-CUC1-01		Charging/Communication Cable	<ul style="list-style-type: none"> ► Can be used for charging and updating firmware - NOTE: Cable is not recommended for routine charging. ► USB-A to Micro-USB connectors ► Cable is 36" long ► Micro USB cable 25-MCXUSB-01R may also be used. Other Zebra USB cables (i.e. 25-124330-01R) may not fit into the USB port on the HS3100. 	

Audio Cables (for HS2100)				
Part Number	Picture	Description	Notes	Required Items
CBL-HS2100-3MS1-01		HS2100 Standard Cable (3.5 mm jack)	<ul style="list-style-type: none"> ▶ 3.5mm barrel jack connector ▶ For use with TC7X, TC8000, or other devices using a 3.5mm barrel jack audio connector ▶ Cable is 43" (1.1 M) long ▶ Rugged cable with rugged connectors that are keyed for failsafe connectivity ▶ Includes one clothing clip. Additional clips can be purchased separately. 	
CBL-HS2100-12S1-02		HS2100 Headset to WT6000 cable (12 pin)	<ul style="list-style-type: none"> ▶ Connects HS2100 directly to WT6000 ▶ 43" long straight cable ▶ Includes one clip for attaching to clothing. Additional clips can be purchased separately. 	
CBL-HS2100-12S1-01		HS2100 to WT6000 Cable (12 Pin)	<ul style="list-style-type: none"> ▶ For use with WT6000 ▶ Cable is 43" (1.1 M) long ▶ Rugged cable with rugged connectors that are keyed for failsafe connectivity ▶ Includes one clothing clip. Additional clips can be purchased separately. 	
CBL-HS2100-QDC1-02		HS2100 to Quick Disconnect Cable	<ul style="list-style-type: none"> ▶ For use when connecting HS2100 to devices using Quick Disconnect cables. ▶ Rugged cable with rugged connectors that are keyed for failsafe connectivity ▶ Includes one clothing clip. Additional clips can be purchased separately. ▶ Cable length is approximately 33" (84 cm). ▶ Has improved quick disconnect connector and strain relief vs. CBL-HS2100-QDC1-01. 	
Headband Modules				
Part Number	Picture	Description	Notes	Required Items
HSX100-OTH-HB-01		Over the Head (OTH) Headband Module	<ul style="list-style-type: none"> ▶ Compatible with both HS2100 and HS3100 ▶ Includes Headband, T-Bar with pad, and Foam Earpad ▶ Order when multiple users would like to share the same Boom Module. Each user will have the own Headband Module and will install the shared Boom Module on it. 	

HSX100-BTN-L-HB-01		Behind the Neck (BTN) Headband Module - Left	<ul style="list-style-type: none"> ► Compatible with both HS2100 and HS3100 ► Includes Headband, T-Bar with pad, and Foam Earpad ► Earpad and microphone will be positioned on Left ear ► Order when multiple users would like to share the same Boom Module. Each user will have the own Headband Module and will install the shared Boom Module on it. 	
--------------------	---	---	--	--

Replacement Items

Part Number	Picture	Description	Notes	Required Items
KT-HSX100-MWS1-50		Replacement Windssocks to cover microphone	► Pack of 50	
KT-HSX100-EPF1-20		Replacement Earpads (Foam cushion)	<ul style="list-style-type: none"> ► Pack of 20 ► Foam cushion material 	
KT-HSX100-EPL1-20		Replacement Earpads (Leatherette material)	<ul style="list-style-type: none"> ► Pack of 20 ► Leatherette material 	
KT-HSX100-OTH1-10		Replacement Headband - Over-The-Head	<ul style="list-style-type: none"> ► Headband only. Does not include T-Bar Pad or Ear Cushion ► Pack of 10 	
KT-HSX100-BTNL1-10		Replacement Headband - Behind-The-Neck - Left side	<ul style="list-style-type: none"> ► Neckband only. Does not include Ear Cushion ► Pack of 10 	
KT-HSX100-TBP1-20		T-Bar with Pad Pack	► Pack of 20	
KT-HS2100-CC1-20		Cable Cord Clips	<ul style="list-style-type: none"> ► For use with HS2100 Audio Cables ► Each Audio Cable includes one Cable Cord Clip. Some users may prefer additional clips to further keep the cable out of the way. ► Pack of 20 	

Charging

Part Number	Picture	Description	Notes	Required Items
SAC-HS3100-B8-01		HS3100 8-Slot Battery Charger	<ul style="list-style-type: none"> ▶ Will charge up to eight HS3100 batteries. ▶ Uses ShareCradle design 	<ul style="list-style-type: none"> ▶ Power Supply (PWR-BGA12V50W0WW and CBL-DC-388A1-01) ▶ AC Line Cord (23844-00-00R)
SAC-HS3100-B8W8-01		HS3100 8-Slot Battery Charger and WT6000 8-Slot Charger	<ul style="list-style-type: none"> ▶ Will charge up to eight HS3100 batteries and up to eight WT6000 units ▶ Uses ShareCradle design 	<ul style="list-style-type: none"> ▶ DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) ▶ AC Line Cord (23844-00-00R)
BRKT-SCRD-SMRK-01		Multi-Slot ShareCradle Mounting Bracket	<ul style="list-style-type: none"> ▶ Allows for rack and wall mounting of one Multi-Slot ShareCradle OR up to four 8-Slot Battery Chargers. ▶ Bracket can be mounted on standard 19" network rack or on a wall. ▶ Provides cable routing slots and removable power supply tray that stores and conceals power supplies. ▶ Adjustable tabs & screw mounts for easy hanging/installation. ▶ Adjustable orientations: <ul style="list-style-type: none"> - 25° High Density (5-Slot Charge Only Cradle) - Horizontal (5-Slot Ethernet Cradle, Single Slot Cradles, and 4-Slot Battery Chargers). ▶ See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket. 	

Power Cords/Power Supplies

Part Number	Picture	Description	Notes	Required Items
CBL-DC-388A1-01		DC Power Cord	<ul style="list-style-type: none"> ▶ Used along with Power Supply PWR-BGA12V50W0WW to power 8-Slot Battery Charger. ▶ Cable length is 1.8 meters 	
PWR-BGA12V50W0WW		Power Supply	<ul style="list-style-type: none"> ▶ Used to power 8-Slot Battery Charger ▶ 100-240 VAC, 12V, 4.16A, 50W ▶ Provides US DOE Level VI compliance for power efficiency. ▶ Replaces PWRS-14000-148R 	DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-00-00R)
KIT-PWR-12V50W		Power Supply Kit	<ul style="list-style-type: none"> ▶ Includes Power Supply (PWR-BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01) ▶ Used along with Power Supply PWR-BGA12V50W0WW to power 8-Slot Battery Charger. 	AC Line Cord (23844-00-00R)

CBL-DC-382A1-01		DC Power Cord	<ul style="list-style-type: none"> ► Used with Power Supply PWR-BGA12V108W0WW to power WT6000/HS3100 Charger. 	
PWR-BGA12V108W0WW		Power Supply	<ul style="list-style-type: none"> ► Used to power WT6000/HS3100 Charger ► 100-240 VAC, 12V, 9A, 108W ► Provides US DOE Level VI compliance for power efficiency. ► Replaces PWRS-14000-241R 	CBL-DC-382A1-01 and 23844-00-00R
23844-00-00R		AC Line Cord		
Batteries				
BTRY-HS3100-HS1-01 (single) BTRY-HS3100-HS1-08 (pack of 8)		Spare Battery (220 mAh)	<ul style="list-style-type: none"> ► Provides up to 15 hours device usage 	